CorePro LEDcapsule LV

CorePro LEDcapsuleLV 1.7-20W G4 830

The CorePro LEDcapsule is a true alternative to the halogen capsule. It is particularly suitable for task lighting and decorative applications in homes, shops, hotels and restaurants. Compatible with existing fixtures with G4 holders and designed for retrofit replacement of halogen capsules, CorePro LEDcapsule delivers huge energy savings and minimizes maintenance costs without any compromise on light quality.

Product data

General Information

Cap-Base	G4 [G4]
Nominal Lifetime (Nom)	15000 h
Switching Cycle	50000X
Technical Type	1.7-20W

Light Technical

Color Code	830 [CCT of 3000K]
Luminous Flux (Nom)	205 lm
Luminous Flux (Rated) (Nom)	205 lm
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	120.00 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical

Power (Rated) (Nom)	1.7 W
Lamp Current (Nom)	240 mA
Wattage Equivalent	20 W
Starting Time (Nom)	0.5 s

Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.5
Voltage (Nom)	12 V

Temperature

T-Case Maximum (Nom)	56 °C

Controls and Dimming

Dimmable	No

Approval and Application

Suitable For Accent Lighting	No
Energy Efficiency Label (EEL)	A++
Energy Consumption kWh/1000 h	2 kWh

Product Data

Full product code	871869679308400
Order product name	CorePro LEDcapsuleLV 1.7-20W G4 830
EAN/UPC - Product	8718696793084
Order code	929001844202
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12

CorePro LEDcapsule LV

Material Nr. (12NC)	929001844202
Net Weight (Piece)	0.008 kg

Dimensional drawing

Product	D	C
CorePro LEDcapsuleLV 1.7-20W G4 830	14.5 mm	38 mm

Capsule 12V2W-20W 200lm N.AD 3000K G4

Photometric data

(cd/1000lm)   0°

— 0-180°   — 90-270°

LEDcapsule CorePro 0.9-10W G4 Capsule 827 ND

LEDcapsule CorePro 0.9-10W G4 Capsule 830 ND

CorePro LEDcapsule LV

Lifetime

LEDcapsule CorePro 0.9-10W G4 Capsule 830 ND

LEDcapsule CorePro 0.9-10W G4 Capsule 830 ND