

## T5 Standard Short

F8W/T5/33-640  
0000021



### PRODUCT OVERVIEW

IPC Code	0000021
Product name	F8W/T5/33-640
Technology	Fluorescent
Watt (Rated) (W)	7.30
Lamp shape	Tubular shape
Cap/Base	G5
Lamp finish	Frosted/Coated
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
Certifications	EUERL002
ETIM Class	EC000108
E-number FI	4942351
E-number SE	8356710
E-number Norway	3822411
Luminous flux (lm)	400
Rated lamp efficacy 100h 50Hz at 35°C (lm/W)	55
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	64
Wattage (W)	8.00
Product Voltage (V)	56
Dimmable	Yes
Average life (Nominal) (h)	10000
Product EAN number	5410288000213

### DATA TABLE

#### General data

IPC Code	0000021
Product name	F8W/T5/33-640
Technology	Fluorescent
Watt (Rated) (W)	7.30
Lamp shape	Tubular shape

## T5 Standard Short

F8W/T5/33-640

0000021

Cap/Base	G5
Lamp finish	Frosted/Coated
Fixture rating	Open
General application	Education,Hospitality,Logistics & Industry,Museums & Galleries,Office,Retail,Residential & Consumer
Certifications	EUERL002
ETIM Class	EC000108
E-number FI	4942351
E-number SE	8356710
E-number Norway	3822411

### Optical data

Luminous flux (lm)	400
Luminous flux (Rated) (lm)	400
Rated lamp efficacy 100h 50Hz at 35°C (lm/W)	55
Rated lamp efficacy 100h 50Hz at optimum temp. (lm/W)	55
Rated lamp efficacy 100h HF at 25°C (lm/W)	55.00
Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	4000
Light colour	Cool White
Colour Code	640
CRI (Ra)	64
Adjustable chromaticity	N
Rated lumen maint. factor (%) at 2000 h 50Hz	0.88
Rated lumen maint. factor (%) at 4000 h 50Hz	0.82
Rated lumen maint. factor (%) at 6000 h 50Hz	0.78
Rated lumen maint. factor (%) at 8000 h 50Hz	0.75

### Electrical data

Wattage (W)	8.00
Watt (Rated) - High frequency (W)	7.1
Current (A)	0.145
Product Voltage (V)	56
Control gear required	Yes
Transformer required	No
Dimmable	Yes
Drive current (mA)	145
Lamp Energy Label (class)	A
kWh per 1000 hours burning time	9

### Lifetime data

Average life (Nominal) (h)	10000
Average life (Rated) (h)	10000

## T5 Standard Short

F8W/T5/33-640

0000021

Rated survival factor (%) at 2000 h 50Hz	1.00
Rated survival factor (%) at 4000 h 50Hz	0.99
Rated survival factor (%) at 6000 h 50Hz	0.96
Rated survival factor (%) at 8000 h 50Hz	0.83

### Physical data

Nominal Product Length (mm)	300.0
Nominal Product Diameter (mm)	16
Max. Length base to base (mm) - A	288.3
Length base to pin Min-Max (mm) - B	293.0-295.4
Max. Lamp Length (mm) - C/L	302.5
Max. Lamp Diameter (mm) - D	17.0
Weight (kg)	0.028


### Packaging

Single packaging type	Carton
Product EAN number	5410288000213
Packaging single length / height (cm)	30.6
Packaging single width (cm)	1.9
Packaging single depth (cm)	1.9
DUN14 (inner)	25410288000217
Units per inner package	25
Packaging inner length / height (cm)	32.2
Packaging inner width (cm)	10.0
Packaging inner depth (cm)	10.0
DUN14 (outer)	15410288000210
Units per outer package	500
Packaging outer length / height (cm)	51.2
Packaging outer width (cm)	33.0
Packaging outer depth (cm)	40.8

### Safety data

Lamp mercury content (mg)	2.30
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	No
Intended purpose	General lighting
Suitable for household illumination	Yes

## TECHNICAL DRAWINGS



## T5 Standard Short

F8W/T5/33-640

0000021

